

## Methods and devices for ultrasound scanning

In patients who are obese or exhibit signs of pulmonary disease, standard transthoracic scanning may yield poor quality cardiac images. For these conditions, two-dimensional transesophageal echocardiography (TEE) is established as an essential diagnostic tool. Current techniques in transesophageal scanning, though, are limited by incomplete visualization of cardiac structures in close proximity to the transducer. Thus, a new method and system which propose a 2D curvilinear array for 3D transesophageal echocardiography in order to widen the field of view and increase visualization close to the transducer face. In this project, a 440 channel 5 MHz two-dimensional array with a 12.6 mm aperture diameter on a flexible interconnect circuit has been molded to a 4 mm radius of curvature. A 75% element yield was achieved during fabrication and an average  $-6\text{dB}$  bandwidth of 30% was observed in pulse-echo tests. Using this transducer in conjunction with modifications to the beam former delay software and scan converter display software of the 3D scanner, cylindrical real-time curvilinear volumetric scans of tissue phantoms was obtained, including a field of view of greater than  $120^\circ$  in the curved, azimuth direction and  $65^\circ$  phased array sector scans in the elevation direction. These images were achieved using a stepped subaperture across the cylindrical curvilinear direction of the transducer face and phased array sector scanning in the noncurved plane. In addition, real-time volume rendered images of a tissue mimicking phantom with holes ranging from 1 cm to less than 4 mm have been obtained. 3D color flow Doppler results have also been acquired. This configuration can theoretically achieve volumes displaying  $180^\circ$  by  $120^\circ$ . The transducer is also capable of obtaining images through a curvilinear stepped subaperture in azimuth in conjunction with a rectilinear stepped subaperture in elevation, further increasing the field of view close to the transducer face.

### Publications

- Pua, E. C., Yen, J. T., & Smith, S. W. (2003). Real-Time Cylindrical Curvilinear 3-D Ultrasound Imaging. Ultrasonic Imaging, 25(3), 137-150.

# Duke

## LICENSING & VENTURES

### Duke File (IDF) #

T-001570

### Inventor(s)

- Yen, Jesse
- Light, Edward
- Pua, Eric
- Smith, Stephen

### College

Pratt School of Engineering

### For more information please contact

Koi, Bethany  
919-681-7552  
[bethany.koi@duke.edu](mailto:bethany.koi@duke.edu)

## Patents

Patent Number: 6,641,534 B2

Title: Methods and Devices for Ultrasound Scanning by Moving Subapertures of Cylindrical Ultrasound transducer Arrays in Two Dimensions

Country: United States of America